



90° ELBOW FEMALE SWIVEL BSP 60° CONE



Reference No.	Thread Size	Hose Size	Dimensions in mm				
	T	Inch	A	H±2.5	B	ØD	1
BA64801-04-04	G.1/4"-19	1/4	29.5	29.0	5.5	3.0	17
BA64801-06-05	G.3/8"-19	5/16	32.0	27.5	6.0	5.0	22
BA64801-06-06	G.3/8"-19	3/8	36.5	31.5	6.0	6.0	22
BA64801-08-06	G.1/2"-14	3/8	36.5	32.0	6.5	6.0	27
BA64801-08-08	G.1/2"-14	1/2	45.0	36.5	6.5	7.0	27
BA64801-10-10	G.5/8"-14	5/8	53.5	53.5	7.5	10.0	27
BA64801-12-10	G.3/4"-14	5/8	53.5	55.0	9.5	10.0	32
BA64801-12-12	G.3/4"-14	3/4	61.5	59.5	9.0	13.0	32
BA64801-16-16	G.1"-11	1	79.5	76.0	10.5	20.0	38
BA64801-20-20	G.1.1/4"-11	1.1/4	90.5	83.5	11.5	25.0	50
BA64801-24-24	G.1.1/2"-11	1.1/2	108.0	98.5	12.5	31.0	55

STRAIGHT MALE METRIC/BSP WITH 60° CONE



Reference No.	Thread Size	Hose Size	Dimensions in mm			
	T	Inch	A	B	ØD	1
MN62201-04-04	G.1/4"-19	1/4	25.5	11.0	4.0	17
MN62201-05-05	G.1/4"-19	5/16	26.0	11.0	5.0	17
MN62201-06-06	G.3/8"-19	3/8	28.0	12.0	7.5	19
MN62201-08-08	G.1/2"-14	1/2	31.0	14.0	10.0	24
MN62201-10-10	G.5/8"-14	5/8	33.0	16.0	13.5	24
MN62201-12-12	G.3/4"-14	3/4	35.5	16.0	16.5	32
MN62201-16-12	G.1"-11	3/4	39.5	19.0	16.5	36
MN62201-16-16	G.1"-11	1	41.0	19.0	22.0	36
MN62201-20-16	G.1.1/4"-11	1	45.0	20.0	22.0	46
MN62201-20-20	G.1.1/4"-11	1.1/4	46.5	20.0	28.5	46
MN62201-20-24	G.1.1/4"-11	1.1/2	48.0	22.0	32.0	50
MN62201-24-24	G.1.1/2"-11	1.1/2	49.5	22.0	33.0	50
MN62201-32-32	G.2"-11	2	54.0	25.0	46.0	65