

CHEMICAL HOSE LL*

ID		OD	Working Pressure		Bursting Pressure		Bending Radius		Max. Coil Length
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	MTR
19	3/4	31	12	170	48	700	152	6	100+
25	1	38	12	170	48	700	203	8	100+
31	1.1/4	45	12	170	48	700	215	9	50
38	1.1/2	52	12	170	48	700	254	10	50
50	2	68	12	170	48	700	355	14	40

TUBE:

Synthetic rubber tube, EPDM, White & Black

REINFORCEMENT:

Braided high tensile yarn

COVER

Perforated synthetic rubber cover, EPDM

TEMP RANGE:

-30°C to +100°C

APPLICATIONS:

For conveyance of a wide range of chemcials such as acid alkalies inorganic in salt and alcoholic materials

PROPERTIES:

Chemical resistant Uniform Thickness Flexible

STANDARD COLOUR:

Inner Tube - Black, White Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Chemro Chemical Hose I.D. W.P. India



Specification Subject to change due to Improvement in Quality (E&O.E).



In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.