

## CNG HOSE

ID		OD	Working Pressure		Bursting Pressure		Bending Radius	
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch
7.90*	5/16	14.50	3.4	50	17.2	250	76	3.00
9.50	3/8	16.00	3.4	50	17.2	250	76	3.00
12.70	1/2	20.00	2.4	35	12	175	101	4.00
19.10	3/4	29.00	2.4	35	12	175	152	6.00
25.10	1	35.00	2.4	35	12	175	178	7.00

\*ARAI Approved

**TUBE:**

Low permeation synthetic rubber

**REINFORCEMENT:**

Single braided high tensile yarn

**COVER:**

Perforated synthetic rubber cover.

**TEMP RANGE:**

-40°C to +100°C Approx

**APPLICATIONS:**

For use in motor vehicles with CNG Installations

**PROPERTIES:**

Resistant to methane & other alkanes  
Uniform Thickness  
Flexible

**STANDARD COLOUR:**

Inner Tube - Black  
Outer Cover - Black

**MARKING ON THE HOSE:**

Indo-Maksson - CNG Hose I.D. W.P.  
Made in India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.