

PNEUMATIC TOOL HOSE 20

ID		OD	Working Pressure		Bursting Pressure		Max. Length
mm	Inch	mm	BAR	PSI	BAR	PSI	MTR
31	1.1/4	43	20	300	65	940	40/LL
38	1.1/2	50	20	300	65	940	40/LL
50	2	66	20	300	65	940	40/LL
63	2.1/2	79	20	300	65	940	40
75	3	93	20	300	65	940	40
100	4	118	20	300	65	940	40

TUBE:

Specially Compounded Synthetic Rubber resistant to oil mist, Black

REINFORCEMENT:

High strength synthetic plies

COVER:

Black rubber cover. Wrap Finish

TEMP RANGE:

-30°C to +82°C Approx

APPLICATIONS:

For heavy duty applications in industries & pneumatic tools that use compressed air applications

PROPERTIES:

Seamless
Heavy Duty
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

Exceeds IS 446 - Type II

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Pneumatic Tool Hose I.D. W.P.
Made in India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.