

PNEUMATIC TOOL HOSE LL*

ID		OD	Working Pressure		Bursting Pressure		Bending Radius		Weight	Max. Length
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	KG/MTR	MTR
6.00	1/4	15.00	14	200	56	800	76	3.00	0.19	100+
8.00	5/16	16.00	14	200	56	800	102	4.00	0.25	100+
10.00	3/8	18.00	14	200	56	800	102	4.00	0.28	100+
12.50	1/2	22.00	14	200	56	800	127	5.00	0.36	100+
19.00	3/4	29.50	14	200	56	800	152	6.00	0.58	100+
25.40	1	37.00	14	200	56	800	203	8.00	0.77	100
31.00	1.1/4	43.50	14	200	56	800	254	10.00	1.00	50
38.00	1.1/2	51.50	14	200	56	800	305	12.00	1.20	50
50.00	2	65.00	14	200	56	800	305	12.00	1.80	40

TUBE:

Specially Compounded Synthtic Rubber, Black

REINFORCEMENT:

Braiding of high strength synthetic fibre

COVER:

Black rubber cover. Wrap Finish.

TEMP RANGE:

-30°C to +82°C

APPLICATIONS:

For all types of industries & pneumatic tools that use compressed air applications.

PROPERTIES:

Seamless
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

IS 446 - Type II

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Pneumatic Tool Hose I.D. W.P.
Made in India



*Long Length

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.