

PRESSURE WASH HOSE 6K

(I)		OD	Working Pressure		Bursting Pressure		Bending Radius		△ Weight
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	KG/MTR
6.7	1/4	13.6	415	6000	1245	18000	75	3.0	0.36
8.2	5/16	15.3	415	6000	1245	18000	85	3.3	0.37
9.8	3/8	17.4	415	6000	1245	18000	90	3.5	0.44

TUBE:

Black colour, synthetic rubber resistant to hot water

REINFORCEMENT:

Double steel wire braids

COVER: Wrap and Smooth

Black Colour, Synthetic Cover resistant to abrasion and weather, oil & Doone. Available in other colours – Blue, Red, Grey and also Smooth Finish Cover on request

TEMP RANGE:

-10°C to + 155°C approx

APPLICATIONS:

For power washer applications with cold and hot water upto 155°C

PROPERTIES:

Flexible High Pressure Multiple Colours Smooth Finish

APPLICABLE STANDARDS:

Indo-Maksson Proprietory

MARKING ON THE HOSE:

Indo-Maksson - HYDRO - Pressure Washer Hose 6K I.D W.P Made in India



Specification Subject to change due to Improvement in Quality [E&O.E].

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.