

ROCK DRILL WB

ID		OD	Working Pressure		Bursting Pressure		Bending Radius	
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch
20.00	3/4	27.50	60	870	240	3480	152	6.00
25.00	1	36.50	50	725	200	2900	201	7.90
31.00	1.1/4	44.00	50	725	200	2900	254	10.00
38.00	1.1/2	50.00	50	735	200	2900	304	12.00
50.00	2	63.50	40	580	160	2320	355	14.00
63.00	2.1/2	80.00	40	580	160	2320	762	30.00
75.00	3	94.00	40	580	160	2320	914	36.00

TUBE:

Special compound of NBR rubber, Black

REINFORCEMENT:

Single braided high tensile wire

COVER:

Specially compounded abrasion & mist resistant black nitrile rubber

TEMP RANGE:

-30°C to +82°C

APPLICATIONS:

For heavy duty, high pressure application in the industrial construction, heavy mining, crusher zones and other rugged conditions

PROPERTIES:

Oil & Mist Resistant

APPLICABLE STANDARDS:

Exceeds IS 446 - Type III

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Super Dynamic Rock Drill Hose I.D. W.P.
Made in India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.