

## SAND BLAST HOSE 12

ID		OD	Working Pressure		Bursting Pressure		Max. Coil Length
mm	Inch	mm	Bar	PSI	Bar	PSI	Mtr.
20	¾	34	12	175	36	525	LL
25	1	40	12	175	36	525	LL
31	1¼	48	12	175	36	525	40/LL
38	1½	54	12	175	36	525	40/LL
50	2	72	12	175	36	525	40/LL

**TUBE:**

Specially compounded abrasion resistant natural rubber, high resilience

**REINFORCEMENT:**

High tensile synthetic plies with copper wire

**COVER:**

Black abrasion resistant natural rubber cover. Wrap Finish.

**TEMP RANGE:**

-40°C to +70°C Approx

**APPLICATIONS:**

For shot and sand blasting applications that help in clearing metal surfaces, etching glass or smoothing casting.

**PROPERTIES:**

High Abrasion Resistance  
Seamless  
Uniform Thickness  
Flexible

**APPLICABLE STANDARDS:**

IS 5894

**STANDARD COLOUR:**

Inner Tube - Black  
Outer Cover - Black

**MARKING ON THE HOSE:**

Indo-Maksson Tough Line Sandblast Hose 12  
I.D. W.P. India



Specification Subject to change due to Improvement in Quality (E&O.E).  
In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.