

SANDBLAST HOSE LL*

ID		OD		Working Pressure		Bursting Pressure		Bending Radius		Weight	Max. Length
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	KG/MTR	MTR	
12.50	1/2	24.00	7	100	35	500	203	8.00	0.5	100+	
20.00	3/4	35.00	7	100	35	500	203	8.00	1.00	100+	
25.00	1	41.00	7	100	35	500	304	12.00	1.30	100	
31.00	1.1/4	47.00	7	100	35	500	304	12.00	1.74	50	
38.00	1.1/2	58.00	7	100	35	500	457	18.00	1.90	50	
50.00	2	70.00	7	100	35	500	508	20.00	2.80	40	

TUBE:

Specially compounded abrasion resistant natural rubber, high resilient

REINFORCEMENT:

Single braided high tensile yarn with copper wire

COVER:

Black abrasion resistant natural rubber cover. Wrap Finish.

TEMP RANGE:

-40°C to +70°C Approx

APPLICATIONS:

For shot and sand blasting applications that help in clearing metal surfaces, etching glass or smoothing casting

PROPERTIES:

High Abrasion Resistance
Seamless
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

IS 5894 - Type I & Type II

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Sandblast Hose I.D. W.P.
Made in India



*Long Length

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.