

## SLURRY SUCTION HOSE

ID		OD	Working Pressure		Bursting Pressure		Bending Radius	Max. Coil Length
mm	Inch	mm	Bar	PSI	Bar	PSI	mm	Mtr.
31	1¼	44	10	150	30	435	190	40/LL
38	1½	51	10	150	30	435	230	40/LL
50	2	64	10	150	30	435	310	40/LL
63	2½	78	10	150	30	435	380	40
75	3	91	10	150	30	435	460	40
100	4	119	10	150	30	435	610	40
125	5	146	10	150	30	435	760	40
150	6	173	10	150	30	435	920	40

**TUBE:**

Specially compounded abrasion resistant natural rubber, high resilient

**REINFORCEMENT:**

High tensile synthetic plies with helix wire and copper wire

**COVER:**

Black abrasion resistant natural rubber cover. Wrap Finish

**TEMP RANGE:**

-40°C +70°C Approx

**APPLICATIONS:**

For suction and discharge of bulk material like cement, gravel and sand etc. in construction industry

**PROPERTIES:**

High Abrasion Resistance  
Seamless  
Uniform Thickness  
Flexible

**APPLICABLE STANDARDS:**

Indo-Maksson Proprietary

**STANDARD COLOUR:**

Inner Tube - Black  
Outer Cover - Black

**MARKING ON THE HOSE:**

Indo-Maksson Tough Line - Slurry Suction Hose  
I.D. W.P. Made in India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice. All products can be customized as per customer requirement in terms of working pressure and special ID & OD requests\*