

SUPER SPRAY HOSE

ID		OD		Working Pressure		Bursting Pressure		Bending Radius		Weight	Max. Length
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	KG/MTR	MTR	
8.00	5/16	18.50	37.5	540	150	2200	80	3.14	0.24	100+	
10.00	3/8	20.00	37.5	540	150	2200	102	4.00	0.38	100+	
12.00	1/2	23.50	37.5	540	150	2200	127	5.00	0.39	100+	

TUBE:

Modified Nitrile Rubber Compound, Black

REINFORCEMENT:

Single braided high tensile yarn

COVER:

Modified Nitrile Rubber, Black. Wrap Finish.

TEMP RANGE:

-30°C to +82°C Approx

APPLICATIONS:

For very high pressure spray applications likes pesticides and chemicals in agriculture and forestry.

PROPERTIES:

High Pressure
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

IS 1677 Type 4

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Super Spray Hose I.D. W.P.
Made in India



Specification Subject to change due to Improvement in Quality [E&O.E].

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.