

## WATER DELIVERY HOSE

ID		OD	Working Pressure		Bursting Pressure		Bending Radius	Max. Coil Length
mm	Inch	mm	Bar	PSI	Bar	PSI	mm	Mtr.
31	1¼	41	10	150	30	450	190	40/LL
38	1½	48	10	150	30	450	230	40/LL
50	2	62	10	150	30	450	310	40/LL
63	2½	76	10	150	30	450	380	40
75	3	87	10	150	30	450	460	40
100	4	115	10	150	30	450	610	40
125	5	142	10	150	30	450	760	40
150	6	168	10	150	30	450	920	40
200	8	225	10	150	30	450	1220	40

#### TUBE:

Specially Compunded Synthtic Rubber, Black

#### REINFORCEMENT:

High Strength Synthetic Plies

#### COVER:

Black synthetic rubber cover

#### TEMP RANGE:

-40°C to +70°C

#### APPLICATIONS:

For all heavy duty air and water applications that require seamless conveyance in any industry

#### PROPERTIES:

Seamless  
Uniform Thickness  
Very Strong

#### APPLICABLE STANDARDS:

Indo-Maksson Proprietary

#### STANDARD COLOUR:

Inner Tube - Black  
Outer Cover - Black

#### MARKING ON THE HOSE:

Indo-Maksson Hydro Water Delivery Hose  
I.D. W.P. India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice. All products can be customized as per customer requirement in terms of working pressure and special ID & OD requests\*