

WATER HOSE LL*

ID		OD	Working Pressure		Bursting Pressure		Bending Radius		Weight	Max. Length
mm	Inch	mm	BAR	PSI	BAR	PSI	mm	Inch	KG/MTR	MTR
12.00	1/2	22.00	12	170	36	510	127	10.00	0.36	100
16.00	5/8	26.00	12	170	36	510	140	12.00	0.47	100
20.00	3/4	29.50	12	170	36	510	152	16.50	0.58	100
25.00	1	37.00	12	170	36	510	203	6.00	0.77	100
31.00	1.1/4	43.50	12	170	36	510	254	8.00	1.00	50
38.00	1.1/2	51.50	12	170	36	510	304	10.00	1.20	50
50.00	2	65.00	12	170	36	510	419	12.00	1.80	40

TUBE:

Specially Compounded Synthtic Rubber, Black

REINFORCEMENT:

Braiding of high strength synthetic fibre

COVER:

Black synthetic rubber cover

TEMP RANGE:

-40°C to +70°C

APPLICATIONS:

For all air and water applications that require seamless conveyance in any industry.

PROPERTIES:

Seamless
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

IS 444 - Type I & Type II

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson - Air/Water Hose I.D. W.P.
Made in India



*Long Length

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.