

CEMENT GROUTING HOSE

ID		OD	Working Pressure		Bursting Pressure		Max. Coil Length
mm	Inch	mm	Bar	PSI	Bar	PSI	Mtr.
25	1	31	10	150	30	450	LL
31	1¼	38	10	150	30	450	40/LL
38	1½	48	10	150	30	450	40/LL
50	2	62	10	150	30	450	40/LL
63	2½	75	10	150	30	450	40
75	3	89	10	150	30	450	40
100	4	116	10	150	30	450	40

TUBE:

Specially compounded abrasion resistant natural rubber, high resilience

REINFORCEMENT:

High tensile synthetic plies with helix wire and copper wire

COVER:

Black abrasion resistant natural rubber cover. Wrap Finish

TEMP RANGE:

-40°C to +70°C

APPLICATIONS:

For cement grouting applications at building sites, irrigation projects & construction of roads. Also used for conveying dry and wet concrete mixture and cement

PROPERTIES:

High Abrasion Resistance
Seamless
Uniform Thickness

APPLICABLE STANDARDS:

Exceeds IS 5137 : 1990

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson Tough Line - Slurry Suction Hose
I.D. W.P. India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice. All products can be customized as per customer requirement in terms of working pressure and special ID & OD requests*