

FUEL DISPENSING HOSE

ID		OD		Working Pressure		Bursting Pressure		Bending Radius	Max. Coil Length
mm	Inch	mm	Inch	Bar	PSI	Bar	PSI	bar	Mtr.
19.1	¾	29.5	1.16	16	232	48	696	152	6.0
25.4	1	36.0	1.42	16	232	48	696	203	8.0

TUBE:

Synthetic Rubber inner Tube

REINFORCEMENT:

High Strength steel wire braid

COVER:

Black synthetic rubber cover resistant to weather and petroleum based fuel

TEMP RANGE:

-40°C to +55°C

APPLICATIONS:

For dispensing Petrol & Diesel fuels

PROPERTIES:

Seamless
Uniform Thickness
Flexible

APPLICABLE STANDARDS:

BS EN 1360 TYPE III

STANDARD COLOUR:

Inner Tube - Black
Outer Cover - Black

MARKING ON THE HOSE:

Indo-Maksson Floil Fuel Dispensing Hose
I.D. W.P. India



Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice. All products can be customized as per customer requirement in terms of working pressure and special ID & OD requests*